



GO BEYOND™

Z-1 Design Quick Tuning Chart

Rev. Q10



DOCK SIDE TUNING

Mast Rake	With a 50' tape, have your AP mast rake set a 28' 3.5"
Sidestay Tension	Sidestays hand tight. Do not over tighten
Sidestay Placement	Place sidestay in forward hole on chainplate

ON THE WATER TUNING

CONTROLS	LIGHT (0-9)	MEDIUM (9-16)	HEAVY (17+)
Mast Rake	28' 3.5"	28' 3"	28' 3"
Upper Shroud Tension	Hand tight, less ½ a number	Hand tight	Hand tight, plus ½ a number
Outhaul	Remove wrinkles, slight shelf on foot but adjust for speed. Easing for power is FAST.	No wrinkles, more shelf on foot	Pull to black band, defined shelf on foot
Cunningham	None	Snug in the puffs, ease in lulls	Full cunningham tension - Hard.
Cunningham/ Outhaul Downwind	Cunningham off/Outhaul eased	Cunningham off/Outhaul eased	Cunningham off/ Outhaul eased
Vang Tension Upwind	No vang tension	Vang tension in puffs until you see overbend wrinkles along mast	Full vang tension. Pull hard!
Vang Tension Downwind	No vang tension	Just enough tension to straighten leech of sail	Play vang downwind w/ waves. Eased when by the lee, pull on when higher
Traveler	Centered	0-4" below center	6-9" below center
Board Height	All the way down, flush with deck	All the way down, flush with deck	2" above deck
Board Height Downwind	¼ way down	¼ way down	¼ way down

This Quick Guide is intended only as a guide to remind you of various approximate settings.